Product data sheet Characteristics

METSECT5CC006

current transformer tropicalised DIN mount 60 5 for cables d. 21



Main

Range	PowerLogic	
Product name	CT	
Product or component type	Current transformer	<u> </u>
Secondary current	5 A	
Accuracy class	Class 1 at 1.25 VA Class 3 at 2 VA	,
[In] rated current	60 A	

Complementary

		2
Current transformer type	Tropicalised for cable	
Current transformer ratio	60/5	_ <u>-</u> ≥
[Ith] conventional free air thermal current	3.6 kA	_ Lidefills p
Dynamic withstand current	2.5 lth	—inim
Maximum safety factor	5	deter
[Ue] rated operational voltage	< 720 V AC 50/60 Hz	d for
[Ui] rated insulation voltage	3 kV	– asn e
Mounting mode	Clip-on By screws	This documentation is not intended as a substitute for and is not to be used for determining suitability or reliab
Mounting support	Mounting plate DIN rail	for and is
Width	44 mm outside:	itute.
Height	65 mm outside:	Subst
Depth	30 mm frame: 37 mm total:	led as a
Diameter	21 mm	ntenc
Net weight	0.19 kg	_ pot
[Uimp] rated impulse withstand voltage	3 kV	- ion
Electrical insulation class	Class B	_ lental
Cable outer diameter	21 mm	_ L
Sealing	With	This d

Environment

Standards	IEC 61869-2 VDE 0414
Product certifications	CE
IP degree of protection	IP20
Relative humidity	095 %
Ambient air temperature for operation	-2560 °C

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	198 g	
Package 1 Height	5.5 cm	
Package 1 width	5.5 cm	
Package 1 Length	8.2 cm	
Unit Type of Package 2	S03	
Number of Units in Package 2	90	
Package 2 Weight	18.217 kg	
Package 2 Height	30 cm	
Package 2 width	30 cm	
Package 2 Length	40 cm	

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information