# Product data sheet Characteristics

# METSECT5MC040

current transformer tropicalised DIN mount 400 5 for bars 10x40 20x32 25x25



		.5
Range	PowerLogic	
Product name	СТ	
Product or component type	Current transformer	<u> </u>
Secondary current	5 A	
Accuracy class	Class 0.5 at 8 VA Class 1 at 10 VA	, et al.
[In] rated current	400 A	

#### Complementary

Current transformer type	Tropicalised for busbar and cable
Current transformer ratio	400/5
[lth] conventional free air thermal current	24 kA
Dynamic withstand current	2.5 lth
Maximum safety factor	5
[Ue] rated operational voltage	< 720 V AC 50/60 Hz
[Ui] rated insulation voltage	3 kV
Mounting mode	Insulated locking screw Clip-on By screws
Mounting support	Busbar DIN rail Mounting plate
Width	70 mm outside: 41 mm inner:
Height	95 mm outside: 41 mm inner:
Depth	45 mm frame: 65 mm total:
Diameter	32 mm
Net weight	0.404 kg
[Uimp] rated impulse withstand voltage	3 kV
Electrical insulation class	Class B

Cable outer diameter	32 mm	
Opening of bars	25.5 x 25.5 40.5 x 10.5 32.5 x 20.5	
Sealing	Without	

#### Environment

Standards	VDE 0414 IEC 61869-2
Product certifications	EAC CE
IP degree of protection	IP20
Relative humidity	095 %
Ambient air temperature for operation	-2560 °C

### Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	400 g	
Package 1 Height	9 cm	
Package 1 width	7.3 cm	
Package 1 Length	12 cm	
Unit Type of Package 2	S03	
Number of Units in Package 2	33	
Package 2 Weight	13.68 kg	
Package 2 Height	30 cm	
Package 2 width	30 cm	
Package 2 Length	40 cm	

## Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins