Product data sheet Characteristics

NSYLAMT5LD1

Cost-effective LED Lamps - 120/230 V AC - 5W



Range of product	Lighting and power sockets	# # # # # # # # # # # # # # # # # # #
Accessory / separate part category	Lighting accessory	
Product or component type	Lamp	
Device application	Multi-purpose	
Device composition	1 lamp 1 fixing elements 2 cable	odelinte for
Power factor	0.9	-

Complementary

Outlet standard	Without socket	
Rated lamp wattage	5 W	
[Ue] rated operational voltage	120/230 V AC 50/60 Hz	
Bulb base	Integral LED	minim inim
Bulb type	LED	
Control type	Built-it switch	
Luminous flux	500 lm	d
Colour temperature	4000 K	
Service life in hours	25000 h	
Electrical connection	Cable quick connector 3 m supplied Cable quick connector 1 m supplied	or sold
Mounting support	Metal parts Cross rails	on botifut
Fixing mode	Magnetic fixing Screws	7 7 7
Range compatibility	Spacial Thalassa	total
Length	310 mm	
Height	30.5 mm	itato
Colour	Aluminium	

Environment

IP degree of protection	IP20 conforming to IEC 60529
Electrical insulation class	Class I
Standards	IEC 60598
Ambient air temperature for operation	-1060 °C
Ambient air temperature for storage	-1665 °C

Packing Units

9	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	530 g
Package 1 Height	6 cm
Package 1 width	7.5 cm
Package 1 Length	34 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	20
Package 2 Weight	11.153 kg
Package 2 Height	28 cm
Package 2 width	35.5 cm
Package 2 Length	42 cm

Offer Sustainability

REACh Declaration	
Yes	
Compliant EU RoHS Declaration	
Yes	
Yes	
Yes	
Regulation China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)	
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	