

SCREW TERMINAL, FUSED, FOR 5X20/25/30MM FUSE, WITH LED 12-30V, 2PTS,

NSYTRV42SF5LD

	,	•	ıc	7	ı	ı	
--	---	---	----	---	---	---	--

Range	Linergy
Product name	Linergy TR
Product or component type	Terminal block
Device short name	TRV
Terminal block type	Fused disconnect
Terminal block level	1
Mounting mode	Clip-on
Nominal cross section	4 mm²
Length	72.5 mm
Colour	Black
Quantity per set	Set of 50

Complementary

<u> </u>	
Fuse size	5 x 20 mm
Width	8.2 mm
Height	56.5 mm
Connections - terminals	1 x screw terminal: upstream 1 x screw terminal: downstream
Number of connections	2
Connection position	Sideways
Number of measurement input	0
Cable cross section	0.24 mm², flexible without cable end 0.24 mm², solid
Tightening torque	0.50.8 N.m
Wire stripping length	8 mm
Tool type	Connection: screwdriver Disconnection: screwdriver
[Ue] rated operational voltage	500 V conforming to EN/IEC 60947-7-1 600 V cURus 600 V CSA
[In] rated current	6.3 A conforming to EN/IEC 60947-7-1 12 A cURus 6.3 A CSA

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Material	Polyamide 6/6: insulating case	
Dielectric loss	0.01 at 1 MHz conforming to IEC 60250 0.01 at 1 MHz conforming to VDE 0303-T4	
Dielectric constant	3.7 at 1 MHz	
Resistivity	10000 M Ω .m conforming to IEC 60093 10000 M Ω .m conforming to VDE 0303-T30	
Surface resistance	1000 G Ω conforming to IEC 60093 1000 G Ω conforming to VDE 0303-T30	
Creep resistance	500 CTI (> 400 kB) conforming to IEC 60093 500 CTI (> 400 kB) conforming to VDE 0303-T30	
Flame retardance	V0, thickness0.8 mm conforming to UL 94	
Net weight	20 g	
Provided equipment	1230 V light indicator	
Range compatibility	Prisma G Prisma P Prisma PH Prisma Pack Spacial Kaedra Pragma TeSys	
Product compatibility	Spacial enclosures	
Environment		
Product certifications	EAC CSA cURus	
Dielectric strength	1000 V conforming to IEC 60243-1	
Ambient air temperature for operation	-40130 °C conforming to IEC 60216-1 -40130 °C conforming to VDE 0304-T21	
Packing Units		
Unit Type of Package 1	Db	
Number of Units in Package 1	1	
Package 1 Height	6.5 cm	
Package 1 Width	11.5 cm	
Package 1 Length	31 cm	
Package 1 Weight	18 g	
Unit Type of Package 2	Gyári csomagolás	
Number of Units in Package 2	50	
Package 2 Height	6.5 cm	
Package 2 Width	11.5 cm	
Package 2 Length	31 cm	
Package 2 Weight	988 g	
Unit Type of Package 3	Doboz	
Number of Units in Package 3	400	
Package 3 Height	30 cm	

Mar 16, 2023

Package 3 Width

Package 3 Length

Package 3 Weight

30 cm

40 cm

8.4 kg

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	
RoHS exemption information	Yes	
Environmental Disclosure	Product Environmental Profile	
Halogen content performance	Halogen free plastic parts product	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
Contractual warranty		

Recommended replacement(s)

18 months

Warranty