# Product data sheet Characteristics

# NSYSFP20750T

Spacial SFP 2000x700x500mm, IP 55, RAL7035, glazed door for Prisma P system





#### Main

Spacial
Spacial SF
Prisma application
Suitable enclosure
2000 mm
700 mm
500 mm
Floor-standing
Installing the Prisma Plus System P
2 sliding rails 4 mounting plate bracket 1 structure 1 door 1 locking system with handle: door 1 rear panel 1 roof 4 adaptor upright

#### Complementary

Structure type	Perforated structure with a pitch of 25 mm	-
	Panels and doors built into the structure	
	Formed from a single section	7
	Vertical uprights joined with top and bottom frames	
Door type	Glazed front	
Number of doors	Front: 1 door(s)	
Door opening side	Reversible (120 °)	
Lock type	4 points lock, handle with 5 mm double bar insert front door	
Mounting plate description	Without mounting plate	7
Type of gland plate	Without gland plate	F F

Accessibility for operation	Front Rear Sides of enclosure
Removable parts	Door by screws hinge Rear panel by screws Roof by screws Mounting plate bracket by screws Sliding rail by screws Adaptor upright by screws
Material	Frame: galvanised steel Uprights: galvanised steel Door: Securit glass Door: sheet steel Panels: sheet steel Hinge: zamak Handle: polyamide 6 with 30 % fibre glass
Surface finish	Epoxy-polyester powder
Colour	Enclosure: grey (RAL 7035) Handle: black (RAL 9005)

#### Environment

Standards	IEC 62208
IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262

### Packing Units

DCE	
1 OL	
1	
97 kg	
213 cm	
75 cm	
59 cm	
	213 cm 75 cm

# Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	
Environmental Disclosure	Product Environmental Profile	

# Contractual warranty

Warranty 18 months	
--------------------	--